



CairWear



Smart Technology, Made to Care

## CairWear

Haptic Pendant



**The CairWear is a stylish and non-stigmatising Haptic Pendant. It can be worn comfortably on the wrist or around the neck, allowing individuals to move around their home with confidence, knowing that help is always within reach in the event of an emergency.**

Easy to configure, the CairWear features optional haptic feedback through its built-in vibration function, allowing the vibration alert to be enabled or disabled as required. Visual feedback is also provided via a concealed LED. The unit features a replaceable battery while retaining IP67 water ingress protection, ensuring long-term reliability even in challenging environments.

Features list

- Tactile manual button
- Secondary configuration button (user battery test)
- Traffic light colours indicating battery life status on test
- Wrist and Neck worn wearing options included
- Vibration and LED indication
- Option to enable/disable haptic feedback
- “Easy Press” Over Jacket accessory available
- Silicone wrist strap available

Specifications

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Compatibility         | Various Industry Protocols                              |
| Operating Frequency   | 868 / 869 / 917 MHz / Custom                            |
| Dimensions            | L44mm x W35mm x D11mm                                   |
| Replaceable Battery   | CR2032 Coin Cell                                        |
| Battery Life          | Up to 5 years (protocol dependent)                      |
| Auto Low Battery      | Battery tested daily (protocol dependant)               |
| Wearing Options       | Wrist and neck worn                                     |
| Wireless Range        | Dependent on receiving system & operational environment |
| Weight                | 17g                                                     |
| Waterproof            | IP67 standard                                           |
| Operating Temperature | -10°C to +55°C                                          |
| Compliance            | CE / UKCA / RoHS 2 / RED / FCC                          |
| Warranty              | 24 months                                               |

